



PO BOX 16458 • FRESNO CA 93755

MATERIAL SAFETY DATA SHEET

PRODUCT/TRADE NAME:

CROSSING

I. NAME

PRODUCT/TRADE NAME: CROSSING
EPA REGISTRATION #: 279-3282-2935
CHEMICAL NAME/Common Name:
N-(2,4-dichloro-5-(4-difluoromethyl)-4,5-dihydro-3-methyl-5-oxo-1H-1,2,4-triazol-1-yl(phenyl)methanesulfonamide/Sulfentrazone
Methyl Benzene/Toluene

II. HAZARDOUS INGREDIENTS

	CAS#	OSHA PEL	ACGIH TLV
Sulfentrazone	122836-35-5	NA	NA
Toluene	108-88-3	200 ppm	300 ppm

III. PHYSICAL DATA

SPECIFIC GRAVITY (H₂O = 1): NA
MELTING POINT: NE
VAPOR DENSITY (AIR = 1): NA
% VOLATILES BY VOL.: NA
ODOR: Slightly Musty
APPEARANCE: Light to Dark Brown Granules
FLASH POINT/METHOD: 92 Deg. F TCC
VAPOR PRESSURE (mmHg): NE
SOLUBILITY IN H₂O: Disperses

IV. FIRE & EXPLOSION HAZARD

EXTINGUISHING MEDIA: Water Fog Foam Alcohol Foam
 CO₂ Dry Chemical Other

FIRE FIGHTING PRECAUTIONS & HAZARDS:
Fight fire upwind. Wear positive pressure self-contained breathing apparatus and full protective equipment. Avoid breathing vapors and spray mist. Avoid contact with fallout and runoff. Toxic gases are evolved when material is overheated. Dike to prevent entering drains, sewers and watercourses. Evacuate people downwind from fire.

V. CARCINOGEN STATUS

OSHA NTP IARC No Listing Type:

VI. REACTIVITY

Stable HAZARDOUS POLYMERIZATION
 Unstable May Occur Will Not Occur

AVOID: Excessive heat

HAZARDOUS DECOMPOSITION PRODUCTS: CO_x, NO_x, SO_x, Hf

VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE OF SPILL: Wear appropriate respiratory and personal protective equipment. Sweep or vacuum into an approved disposal container.

DECONTAMINATION: Treat area with detergent and water. Absorb with inert material and place in approved disposal container. Repeat as necessary until area is clean.

ENVIRONMENTAL HAZARDS: Slightly toxic to fish. Dike areas to prevent entering drains, sewers or water courses.

DISPOSAL: Use a DOT-approved container and dispose of in an EPA Class I disposal site.

VIII. HEALTH PRECAUTION DATA

INGESTION: Acute Oral LD₅₀ (rat) 2416 mg/kg (FMC). Do not ingest. Wash thoroughly before eating, drinking or smoking. Do not store near food or feed. May be fatal.

INHALATION: No PEL/TLV. Avoid breathing vapors.

SKIN ABSORPTION: Dermal PEL/TLV LD₅₀ (rat) >5000 mg/kg (FMC). May cause skin irritation. Wear proper personal protective equipment to minimize exposure or spray mist. Wear appropriate respiratory protection for exposures above the PEL/TLV.

EYE EXPOSURE: Avoid eye contact. May cause mild eye irritation. Can be an

eye irritant. Wear proper eye protection to prevent exposure. If contact occurs, flush eyes with water for a minimum of 15 minutes.

EFFECTS OF OVEREXPOSURE: Endosulfan acts primarily on the central nervous system by all routes of exposure. Symptoms of overexposure may include headache, weakness, tremors, nausea, convulsions, diarrhea and respiratory depression. Can be fatal. Chronic exposure may cause kidney and liver damage. Preexisting medical conditions involving the above symptoms may be aggravated by exposure.

FIRST AID: In all cases, get prompt medical attention. If ingested, give several glasses of water. Do not induce vomiting. For skin contact, remove contaminated clothing and wash with soap and water. For eye exposure, flush eyes with water for a minimum of 15 minutes. If inhaled, remove to fresh air and administer CPR if necessary.

IX. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Use NIOSH/MSHA-approved respirator for pesticides for exposures up to 10 times the PEL/TLV. Positive pressure self-containing breathing apparatus should be used for confined space entry and exposure above 10 times the PEL/TLV.

PERSONAL PROTECTIVE EQUIPMENT: Rubber or neoprene boots, nitrile or neoprene gloves, long-sleeved coveralls, hat and safety goggles or glasses with side shields and brow protection and apron where necessary. For manufacture, formulation or application operations, recommend a shower at the end of the work shift.

VENTILATION: Local exhaust ventilation is recommended for manufacture and formulation. Store in a well-ventilated area. Allow closed trucks adequate time to ventilate prior to entering.

X. SPECIAL PRECAUTIONS

Keep out of the reach of children. Read and follow all label instructions. Do not store near sparks, open flame or heat source. This product is corrosive to iron.

XI. REGULATORY DATA

SARA HAZARD CLASS: Acute Chronic Flammable
 Pressure Reactive None

SARA 313: Yes No Chemical: Toluene

SARA 302: Yes No Chemical:

TPQ:

CERCLA: Yes No Chemical: Toluene

RO: 1,000*

RCRA: Yes No

NFPA HAZARD RATING:

Health: [2]

Fire: [1]

Reactivity: [0]

Special: []

HMS CODES:

Health: [2]

Fire: [1]

Reactivity: [0]

NFPA HAZARD RATING SCALE:

0 = Minimal 3 = Serious

1 = Slight 4 = Severe

2 = Moderate

HMS HAZARD RATING SCALE:

0 = Minimal 3 = Serious

1 = Slight 4 = Severe

2 = Moderate

DATE PREPARED: January 7, 2005

REVISED DATE:

Notice: This information was developed from information on the constituent materials. No warranty is expressed or implied regarding the completeness or continuing accuracy of the information contained herein, and Wilbur-Ellis disclaims all liability for reliance thereon. The user should satisfy himself that he has all current data relevant to his particular use.

*Technical Material NE - Not Established NA - Not Applicable
24 Hour Emergency Phone Number
CHEMTREC: (800) 424-9300